

Industrial Display Monitor

5.7" Color TFT Industrial Display Monitor

ADP-1050



Features

- 5.7" TFT VGA LCD
- 640 x 480 (native mode), 220 cd/m²
- Front Panel NEMA 4/IP 65 rating
- Sealed resistive touch screen
- LED long life time backlight
- OSD control
- Viewing Angle: 140 (H), 100 degrees(V)
- DC 12V power input
- Support Panel / VESA 75 mount



Display Specifications

Display	5.7" Color Active TFT Flat Panel Display
Luminance	220 cd/m ²
Viewing Angle	140/100 (H/V)
Resolutions	640 x 480 (native mode), 262K colors
Backlight Lifetime	LED long life-time backlight
Touch Screen	Analog resistive (optional)
OSD Control	On the back side
I/O Connectors	1xDC power input, 1xVGA, optional:DVI,S-Video,RCA, touch (RS-232 or USB)
Power Input	DC 12V only

Mechanical Specifications

Construction	Plastic Housing
Dimensions	204 (W) x 135 (H) x 59mm (D)
Dimensions Cutout (W x H)	192 (W) x 137mm(H)
Mounting	Panel / VESA 75 mount
Weight	1.03kgs

Environment Specifications

Operating Temperature	0~50°C(32~122°F)
Storage Temperature	-20~60°C (-4~140°F)
Relative Humidity	10~90% @40°C Non-condensing, without touch screen
Vibration	1G peak, 5~500 Hz (Random)
Shock	15G peak acceleration (11 msec. duration)
Rating	NEMA 4/IP65 compliant front bezel
Certificate	Meet CE / FCC Class A

Dimensions

