



W-M1B403



Specifications

General

- Power Input Range 10~60VDC
- Power Consumption 2.4W@24VDC
- Watchdog Timer System(1.6 second Fixed) Communication (Programmable)
- Connector 1 x plug-in terminal block (#16 ~ 30 AWG)
- Temperature (Operating) -25~70°C
- Humidity 5~95%
- Temperature (Storage) -30~75°C
- Interface RS-485
- Communication Protocol Modbus/RTU
- Communication Speed Serial: From 1200 to 115.2k bps
- Communication Distance Serial: 1.2km
- Isolation Protection 3000VDC

Digital Output

- Relay Output Channels 4 Form A, 4 Form C
- Contact Rating 5A 250VAC/30VDC
- Dielectric Strength 3KV
- Operate Time 10ms Max.
- Release Time 5ms Max.
- Startup Value Setting Yes
- Communication Safety Value Setting Yes

W-M1B404



Specifications

General

- Power Input Range 10~60VDC
- Power Consumption 3.8W@24VDC
- Watchdog Timer System(1.6 second Fixed) Communication (Programmable)
- Connector 2 x plug-in terminal block (#16 ~ 30 AWG)
- Temperature (Operating) -25~70°C
- Humidity 5~95%
- Temperature (Storage) -30~75°C
- Interface RS-485
- Communication Protocol Modbus/RTU
- Communication Speed Serial: From 1200 to 115.2k bps
- Communication Distance Serial: 1.2km
- Isolation Protection 3000VDC

Digital Output

- Relay Output Channels 8 Form A, 8 Form C
- Contact Rating 5A 250VAC/30VDC
- Dielectric Strength 3KV
- Operate Time 10ms Max.
- Release Time 5ms Max.
- Startup Value Setting Yes
- Communication Safety Value Setting Yes