

10,4" Industrial Panel PC

IPPC 1041



Specification

System

- Board size: Mini-ITX (170x170mm)
- System Fan: 2*(60x60x10mm)
- Speaker: 2*2W Stereo Speaker
- OSD: Brightness, Contrast, H/V Position, Color, Phase, Clock, Management
- Construction: Heavy duty steel & Aluminium (Front panel)
- Dimension: (WxHxD) With front panel: 366x279x130.9 mm
- Dimensions: (WxHxD) W/O front panel: 356x269.5x130.9 mm
- Open frame structure (optional)

LCD

- Display: 10.4" TFT LCD
- Resolution: 800x600
- Max. Colors: 262144 colors
- Luminance: 220cd/m²
- MTBF: 20.000hrs
- Pixel Pitch: 0.264 mm
- Contrast Ratio: 500:1
- Power Consumption: 3.3 W

10.4" Industrial Panel-PC

Features

- High performance PC up to Pentium 4
- 10.4" SVGA TFT LCD
- Modularized system Design
- Resistive Touchscreen (optional)

Configuration:

- System can be equipped with any ITX-Board from 533 MHZ up to 3,6 GHZ
- Special System Configuration by request

Storage

- 6 in 1 card reader (left side)
- Interchangeable slim optical drive (right side)
- 2.5" HDD (1 x) horizontal

Environmental

- Operating temperature: 0° to 60C°
- Storage temperature: - 20C° -80 C°
- Storage humidity: 10% to 90% non condensing
- Vibration: 17 to 500 HZ 1G PTP
- Shock: 1G/peak (11msek)
- Front panel protection: meet NEMA4 & IP 65 (IPPC)

Power Supply

- Input: 115 – 230 VAC, 50/60 HZ
- Output: 350W with PFC

Mounting

- Wall-mount/Desktop stand/swing arm
- Meets standard VESA / 75/100mm) mounting

10,4" Industrial Panel PC

Order Information

- IPPC-1041** Industrial Panel PC with 10.4" TFT LCD and 350W power supply
- IPPC-1041T** Industrial Panel PC with 10.4" TFT LCD, Touch screen and 30W power supply
- OPPC-1041** Open frame Industrial Panel PC with 10.4" TFT LCD and 350W power supply.
- OPPC-1041T** Open frame Industrial Panel PC with 10.4" TFT LCD, Touch screen and 350W power supply.

Dimensions

