

UCON310-I

**Support one Universal RS232/422/485 input to
Ground isolated RS232 interface converter
Major in RS232 application environment
Powerful and Flexible**



- ★ Support data transmission LED display for each port
- ★ Support one Universal RS232/422/485 input to **Ground Isolated** RS232 interface converter.
- ★ Safety in RS232 application environment.
- ★ Easy to set as RS232 to **GROUND** isolated RS232 **isolator**.
- ★ Easy to set as RS422 to isolated RS232 **interface converter**.
- ★ Easy to set as RS485 to isolated RS232 **interface converter**.
- ★ Support Auto Data Direction Control in RS485 interface

UCON310-I specifications :

Serial1 interface :

- ◆ Connector type: DB9 male connector.
- ◆ Can be set to RS232/RS422/RS485 via DIP switch.

NOTE: Serial1 port is same signal ground with power input from power adapter.

NOTE: each port with 5 signal pin TX+ , TX- , RX+ , RX- , isolated GND

NOTE: In RS485 interface type support Auto-Data-Direction-Control feature. TX+ and RX+ short as Data+ signal , TX- and RX- short as Data- signal. User can use TB485 module to exchange DB9 connector to 3 pin terminal block connector.

Serial2 interface:

- ◆ Connector type: DB9 male connector.
- ◆ Ground isolated RS232.

NOTE: Serial2 port is isolated signal ground with power adapter.

Power input :

- ◆ UP110/UP220 5V power adapter.
- ◆ Current consumption: 200mA.

LED indicator :

- ◆ PWR: DC power input ON indicator.
- ◆ **Serial1:** RS232/RS422/RS485 input port1 TXD/RXD signal activity.
- ◆ **Serial2:** Isolated RS232 output port2 TXD/RXD signal activity.

Dimension :

- ◆ UCON310-I box:
92mm (W) * 118mm (L) * 27mm(H)

Environment :

- ◆ operating temperature: 0°C to 55°C
- ◆ operating humidity : 0% to 95% RH.
- ◆ storage temperature : 0°C to 65°C .
- ◆ storage humidity : 5% to 95% RH.


Application :

RS232 to Ground isolated RS232 isolator.
RS485 to GROUND isolated RS232 interface converter.

RS422 to GROUND isolated RS232 interface converter.

Accessories :

TB485 : DB9 Female to RS485 terminal block kit.



Performance upgrade capability and relative products.

- ▲ TWIN485 box: two sets ground isolated RS232 to RS422/485 converter.
- ▲ ULOG310-I box: monitored universal RS232/RS422/RS485 to GROUND isolated RS232 interface converter via USB connection.

©All names are the trademarks of their respective organization.



RAYON TECHNOLOGY CO., LTD.

2F, No. 177, Chung_Shan 2 Rd., Lu_Chou city, Taipei Hsien, Taiwan.

TEL: 886-2-82858362 FAX: 886-2-82857065

E-Mail: rayon@ms1.hinet.net or info@rayontech.com.tw

WEB: <http://www.rayontech.com.tw>

WEB: <http://www.rayontech.com>